



Riding type high speed rice transplanter WE-D60



20-horsepower gasoline engine - easily cope with high-speed operations
2 segment transferred



20 Liters large capacity fuel tank - a long time job guarantee



can isolate the arbitrary grouping clutch - the number of rows change



Walking cut off switch transplanting - safer, more humane



the automotive-style dashboard - information from time to time feedback, at a glance



6 stalls induction regulator - land soft and hard to cope



multi-functional modular switch - more convenient operation



fixed throttle handle - for a long time oil to enhance the operating body



convenient foot throttle - always oil control, more convenient



ultra-wide range of plant spacing adjustment - to adapt to the requirements of each seedling seedlings



four-wheel drive control pedal - powerful climbing



the industry's largest ground clearance - to enhance the performance of paddy fields through



turned to the side of the clutch automatic braking - Reduce mitigate the destruction of plots



wide cab - plus seeding operation more convenient



driven by the electric motor - operating more intelligent multifunction scribe



take seedlings amount, transplanting thickness can be adjusted freely - wide adaptability



the adjustable depth of the floating plate - to adapt to different fields requirements



high-performance rotating transplanter arm - to provide a unified, high-precision flapper



the the lame degree of adaptive swing bracket - easily deal with tilt

Model		WE-D60					
Product Name		Riding type rice transplanter					
Driving Mode		Four-wheel drive					
Size	Length(mm)*Width(mm)*Height(mm)	3000*2080*1520					
	minimum distance from the ground(mm)	430					
	Weight(kg)	620					
Engine	Model	Honda 614 /air-cooled 4-stroke,2-cylinder OHV (gasoline) engine					
	Displacement:L (cc)	0.614(614)					
	Rated output (Ps/rpm)	11/3200					
	Fuel used	Unleaded gasoline above No. 90					
	Fuel tank capacity(L)	20					
	start manner	Electric start					
Transplanting Part	Planting methods	Rotary planting					
	Planting rows/spacing (row/mm)	6/300					
	the amount of adjust number of seedlings per Hole	Horizontal transfer of volume (mm / times)	15.5/18	14/20	10.7/26		
		The depth of vertical take seedling (mm)	8~19(12File)				
	Hill Spacing (cm)	27	23	19	16	14	12
	Hill No.(per 3.3m ²)	40	50	60	70	80	90
	Pieces per hill	2~5adjustable					
Transplanting Speed (m/s)	1.4						
Transplanting Capacity (hm ² /h)	≧0.3						
Fuel consumption (kg/hm ²)	≦6.7						



A Division of Ken-Ding Group
Weizhou International Co., Ltd

Address : No. 24, Lane 135 Wu-de St., Kaohsiung City, Taiwan ROC 80647

Mailing : P. O. Box 1394 kaohsiung City. Taiwan ROC

Tel : 886-7-7169249 Fax : 886-7-2134620

e-Mail : agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/Index-import.htm>

Rapid Communication Facilities as below:

QQ : 1467808036	skype : service450429	Line ; weizhou1995
Wechat : walterhsu1995	whatsapp:+886972326392	Viber : +886972326392
Twintter : weizhou	Linked IN : weizhou	TataoTalk : weizhou1995