樹枝粉碎機 WE-M12D



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The 18" diameter single top feed wheel easily climbs over material, reduces drag and increases chipping efficiency.
- Staggered knife pockets maintain a more consistent chip quality, reduce long slivers, reduce disc wear and use four like chipper knives versus two long and two short in each pocket.
- Like all equipment, the M12D is a long-lasting, durable machine backed by a world-class parts and service support team.



Chipper Disc

37" diameter x 2" thick chipper disc material, ultrasonically tested and certified free of material defects, has four full-length, removeable paddles for maximum chip throwing velocity.



Channel Frame

8.2 lb., 6" Channel frame fully extends beneath the infeed for maximum support.



Infeed System

Folding infeed tray with single (top) feed wheel and straight, flow-through infeed design for more efficient material feed.



Feed Wheel

TorqMax[™] Top Feed Wheel Compression system with springassisted down pressure generates more than 3,200 lb./ft. of material pulling force.

SPECIFICATIONS

PECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

General

Chipping capacity12
Height
Width 5'11"
Length (transport) 16'2"
Length (operating) 17'5"
Gross weight 5,350 lbs
Suspension 6,000 lb. torsion
Infeed opening53" wide x 32" high
Throat opening18" wide x 12" high
Disc 2" thick x 37" diameter
Engine CAT or Kubota
Horsepower 84–99 HF
Fuel capacity 24 ½ gallons
Hydraulic capacity 9 gallons
Frame8.2 lb., 6" channe
Tires(2) 225/75Rx15"
Hitch 21/2" Pintle

Equipment Highlights

Chipper disc with four staggered ½" x 5" x 7 ¼" dual-edged knives and four full-length, bolt-on chip throwing paddles

Folding infeed tray for reduced transport length and increased maneuverability

Quarter disc hood access for disc maintenance and eases serviceability.

 $360\ensuremath{^\circ}$ manual rotation discharge with adjustable chip deflector

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment

Fuel tank sight gauge, drain plug and shutoff valve

Hydraulic tank shut-off valve, drain plug, clean-out cover and vented filter head assembly with dipstick to check oil level

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options

Variable speed flow control Reversing automatic feed system with hydraulic lift assist

Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard Aluminum diamond plate fenders
Custom paint and logo packages

Knife saver tool
Engine stop on infeed

Material pushing tool

Discharge cleanout door on side or bottom Spanish and English safety decals

瑋洲企業有限公司



地址:台灣高雄市前鎮區武德街135巷24號 信件請寄:高雄市郵政信箱1394號 Tel:07-7169249 Fax:07-2134620 E-Mail:agri-machine@weizhou.com.tw

http://www.weizhou.com.tw/Agrimachine/i-chipper/Index.htm Line: weizohu1995 Skype: service450429 QQ: 1467808036 Viber:+886972326392 WhatsApp:+886972326392 Wechat:walterhsu1995