

樹枝粉碎機 WE-M15R



BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders provides maximum chipping efficiency.



Channel Frame

The 8.2 lb., 6" channel frame rails with 2" x 6" tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.



Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,500 lbs. of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 6/29/15

General

Chipping capacity. 15"
 Height 8'11"
 Width 7'3"
 Length 18'1"
 Gross weight (approximate) 8,900 lbs.
 Suspension. 9,000 lb. Torflex
 Infeed opening. 56" wide x 37" high
 Throat opening. 20 1/2" wide x 15" high
 Drum 23 3/4" wide x 30" diameter
 Engines. . . CAT, Cummins, GM, John Deere, Perkins
 Horsepower 130–174 HP
 Fuel capacity 32 gallons
 Hydraulic capacity 12 gallons
 Frame 8.2 lb., 6" channel
 Tires. (2) 215/75R17 1/2"
 Hitch 2 1/2" Pintle Ring

Equipment Highlights

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and direct-drive bottom feed wheel with torque arm coupler

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional pre-plumbed valve section for installation of an aftermarket winch package

3" x 5" tubular steel telescoping drawbar with two 12" extensions

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
 Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
 Bottom Bump Bar
 Hydraulic Swivel Discharge
 Cone Holder
 Spare Tire/Mount
 Folding Infeed Tray
 Flow Control
 Axle Options Available
 Fender Options Available
 Battery Box Options Available



瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號
 信件請寄：高雄市郵政信箱1394號
 Tel：07-7169249 Fax：07-2134620

E-Mail: agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/i-chipper/Index.htm>

Line : weizohu1995 Skype : service450429 QQ : 1467808036

Viber: +886972326392 WhatsApp: +886972326392 Wechat: walterhsu1995