

飛機牽引車

WE-Comet 3 型號



Technical specifications		Serial equipment		
Dead weight	3100 kg	<ul style="list-style-type: none"> ▪ Robust industrial engine ▪ Wear-proof differential axle ▪ Transmission with electrical protection against improper handling ▪ Hydraulic steering system ▪ Dual circuit power-brake with brake booster ▪ Hydraulically ventilated parking brake acting on rear drum brake ▪ 5-fold trailer coupling at the rear (others upon request) ▪ 2 outside rear view mirrors ▪ Hydraulically suspended driver seat individually adjustable ▪ Safety belt ▪ Adjustable steering wheel ▪ Roof light** ▪ Wiper-washing system (front and rear)*** 		
Engine*	<table border="1"> <tr> <td>Deutz-Diesel 36.4 kW (50 HP) EU IIIA</td> <td>Deutz-Diesel 45.9 kW (62 HP) EU IIIA</td> </tr> </table>		Deutz-Diesel 36.4 kW (50 HP) EU IIIA	Deutz-Diesel 45.9 kW (62 HP) EU IIIA
Deutz-Diesel 36.4 kW (50 HP) EU IIIA	Deutz-Diesel 45.9 kW (62 HP) EU IIIA			
Transmission*	<table border="1"> <tr> <td>Automatic Transmission Graziano PST 1</td> <td>Semiautomatic Transmission Graziano PST 2</td> </tr> </table>		Automatic Transmission Graziano PST 1	Semiautomatic Transmission Graziano PST 2
Automatic Transmission Graziano PST 1	Semiautomatic Transmission Graziano PST 2			
Drawbar pull	<table border="1"> <tr> <td>17 kN (1700 kg)</td> <td>21 kN (2100 kg)</td> </tr> </table>	17 kN (1700 kg)	21 kN (2100 kg)	
17 kN (1700 kg)	21 kN (2100 kg)			
Dimensions	length 2895 mm width 1400 mm height 2130 mm			
Miscellaneous*	<ul style="list-style-type: none"> ▪ Small turning circle of approx. 3700 mm ▪ quick and easy access to all important service points and components 	<ul style="list-style-type: none"> ▪ Sun shield for driver*** ▪ Fuel gauge ▪ Working hour meter ▪ Emergency switch-offs ▪ brake pad wear indicator <p>** with closed cab *** only front with open cab</p>		

* other technical equipment on demand