

迷你鏟裝機

ESTATE SERIES



500 4WD
575 TRACK

Mini Skid Loaders - Ideal for Estate Home Owners
and Light Utility and Construction Applications

Line : weizohu1995 Skype : service450429 QQ : 1467808036
<http://www.weizhou.com.tw/Engmachine/i-skidloader/index.htm>

Go Places only RAMROD

Two Great Economical Estate Models To Serve You..



MODEL 500
Four Wheel Drive



MODEL 575
Track Drive

Two models of RAMROD "Hydraulic Self-Propelled" Mini Loaders deliver big performance in small places. Machines are driver-friendly, with an unobstructed view of all working conditions, with quick-learning time, and equipped with Self-Centering Controls which "Stop Dead" all drive, lift, or levelling movements when the operator's hands are removed from the controls. Machines are easily transported in a trailer or pick-up truck.

Choose The Model That Best Suits Your Requirements

RAMROD - 4WD - Electric Start - 4" Tires (30" Wide)
RAMROD - 4WD - Electric Start - 8" Tires (38" Wide)
RAMROD - Electric Start - 6" Tracks (34" Wide)
RAMROD - Electric Start - 9" Tracks (40" Wide)

- Choice of Tire & Track Widths
- Safety Louvered Front Panel Engine Shield
- Tropical Air Flow Cooling
- Lift & Tie Down Lugs
- Enclosed Drive Chain
- Powder Paint Finish
- Dripless Hydraulic Couplers
- Multi - Hour Fuel Capacity



Line : weizohu1995 Skype : service450429 QQ : 1467808036
<http://www.weizhou.com.tw/Engmachine/i-skidloader/index.htm>



RAMROD Mini Loaders Can!

Quick-On-Quick-Off Attachments

Change any of the versatile attachments in seconds reducing downtime and increasing productivity with the right tool.

Safe-Load Self-Levelling Loader

Prevents load “fall back” on operator at full height & eliminates the danger of losing a load during the raising and lowering process.

Superior Bucket Rollback and Dump Angle

20° Rollback Angle lets you easily fill and carry material in bucket. The 80° Dump Angle empties the load completely each time & prevents sticking to bucket.

Easy to Operate Single Hand Palm Steering

RAMROD Exclusive & Unique Single Handed Steering Control System makes this machine very user friendly.



More Features and Benefits to Enhance your Investment

Low Step Non-Slip Stand-On Platform

Safe & easy on /off slip resistant platform with side & rear protection.

Great Lift Height and Lift Capacity

4WD Model 500 Lifts 500 lbs (227 kg) and Track Model 575 lifts 575 lbs (262 kg). Loader lift height to hinge pin is 66” (1690 cm).

Narrow Width Models

Compact 30” Overall width of 4WD model gets machine into confined areas, elevators, doorways, and manoeuvres easily in obstructed areas.

Parts and Service Support - Warranty


Same day processing of parts & service requests from worldwide network of dealers and by factory. 3 year structural warranty of machine frame & arms & 1 year on other manufacturers components.

Auxilliary Hydraulic Outlets (Optional)

Conveniently loaded for easy access on front of lift arms to power various attachments available.



Quick-on, Quick-off Attachments



Material Bucket - 31"-36"-42"



Post Hole Augers



Backhoes - Digs 6'6" with a 9" Reach



Brooms - 24" Dia x 36" Wide Angles - Steel & Poly Bristles



Carry All Leveler - 48" Wide x 24" Deep




42" Dozer Blade



Grapple Bucket



Hay & Manure Fork - 39" Wide with 1 1/4" x 24" Tines



Hydraulic Hammer - 500 to 1300 Blows/minute at up to 184ft/lbs (86gpm)



Loose Material Handler - 35" Wide - Opens 68" Hydraulically



Mini Dipper - 60" Dig, 12" Bucket, 86" Dump Height and 70" Bucket Clearance



Multi-Purpose Tool-bar Ripper - Tow bar, Boom



Pallet Lift Fork - Back Guard with 2 - 41" Tines Max 30" Wide



Ripper - with 2 - 12" Long Teeth




Snow Blower - 35" Wide - 2 Stage - Hydraulic Drive - Adjustable Spout



Tiller - 36" Wide - 6" Deep Forward and Reverse Tine Rotation



Trencher - 24" Cutting Depth 4" to 6" Chain Widths



Tooth Bar - For 31", 36" & 42" Buckets

Specification and Features

Gasoline Engine Horsepower
Traction (Push-Pull) Power
Lift Capacity
Carrying Capacity
Lift Height to Pivot Pin
Hydraulic Pressure
Hydraulic Flow/Aux Outlets
Narrowest Width
Widest Width
Body Height
Length with Bucket
Length less Bucket
Ground Clearance
Rollback Fully Raised
Rollback at Ground
Dump Fully Raised
Dump at Ground Level
Weight

lbs(Kg)
lbs (kg)
lbs (kg)
inches (mm)
PSI (Bar)
GPM (L/Min)
inches (mm)
inches (mm)
inches (mm)
inches (mm)
inches (mm)
inches (mm)
inches (mm)
20°
20°
80°
80°
lbs (kg)

Model 500 4WD

13.5HP
995 (452)
500 (227)
825 (375)
66 (1690)
2100 (144)
6.3 (2.4)
30.0 (762)
38.0 (965)
48.5 (1232)
77.5 (1968)
58.5 (1486)
4.75 (122)
20°
20°
80°
80°
1150 (500)

Model 575 Track

13.5HP
995 (452)
575 (262)
975 (443)
66 (1690)
2100 (144)
6.3 (2.4)
34 (864)
40.0 (1016)
48.5 (1232)
77.5 (1968)
58.5 (1486)
4.75 (122)
20°
20°
80°
80°
1380 (627)



Specifications Subject to Change Without Notice



MADE IN NORTH AMERICA

 **WEIZHOU**

瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號

信件請寄：高雄市郵政信箱1394號

Tel：07-7169249 Fax：07-2134620

E-Mail:eng-machine@weizhou.com.tw