

3005

Power in a small package

Its use in everyday applications has already earned this model the motto „Great performance in a small package“. A powerful, quiet, space-saving model, versatile, either for gentle movement of liquids or vigorous mixing of the most varying materials. This unit is maintenance-free, carries the GS safety approval and comes with the CE mark.



3005 Analogue Orbital Shaker with Universal Mount 3952

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for continuous operation
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ clearly laid out control panel for easy operation

Technical Data

Overall dimensions (W x D x H):
380 x 510 x 140 mm

Moving platform: 330 x 330 mm

Load: max. 8 kg

Shaking motion: orbital

Timer: up to 60 minutes, or continuous operation

Shaking amplitude: 10 mm

Shaking frequency: 20 - 500 rpm

Electrical connection:

230 V* 50..60 Hz, 65 W

* Other voltages on request!

Net/gross weight: 10/12 kg

Packing volume (cardboard box): 0.1 m³

■ **Order No. 3005**

- ▶ electronic speed control, stepless, with gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

This compact Orbital Shaker proves its performance capability in daily use in biology and microbiology laboratories and in diagnostic test reactions.

Also used in laboratories, incubation rooms and moderating rooms at ambient temperatures between +10 °C and +50 °C.

Space-saving and versatile

What sets this robust, space-saving compact Shaker apart from the 3005 Shaker is its shaking motion. Its impressive features are both its gentle back-and-forth motion and its intensive shaking of liquids, especially in separating funnels. This unit is maintenance-free, carries the GS safety approval and comes with the CE mark.

3006



3006 Analogue Reciprocating Shaker with Tray 3950 and Clamps for separating funnels 3955 - 3959

Technical Data

Overall dimensions (W x D x H):
380 x 510 x 140 mm

Moving platform: 330 x 330 mm

Load: max. 8 kg

Shaking motion: reciprocating
(back and forth)

Timer: up to 60 minutes, or continuous
operation

Shaking amplitude: 20 mm

Shaking frequency: 20 - 300 rpm

Electrical connection:

230 V* 50...60 Hz, 65 W

* Other voltages on request!

Net/gross weight 10/12 kg

Packing volume (cardboard box): 0.1 m³

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for continuous operation
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ clearly laid out control panel for easy operation

- ▶ electronic speed control, stepless, with gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

This Shaker can be used in medical diagnostics or analysis, as well as for growing micro-organisms, cell and tissue cultures.

This unit is used particularly in laboratories, incubation rooms and moderating rooms at ambient temperatures between +10 °C and +50 °C.

■ **Order No. 3006**

3011 / 3012

Gentle and quiet

Gentle and uniform rocking motion make this quiet unit stand out in every-day use. Both of these units are maintenance-free, carry the GS safety approval and come with the CE mark.



3011 Analogue Orbital Rocking Motion Shaker with Non-slip Mat 3965

Technical Data

Overall dimensions (W x D x H):
510 x 625 x 168 mm

Moving platform: 450 x 450 mm

Load: max.15 kg

Shaking motion: three-dimensional orbital rocking

Timer:

3011 / up to 60 minutes, or continuous operation

3012 / 1 min. - 99:59 hours, or continuous operation

Shaking amplitude: 3 degrees

Shaking frequency: 2 - 50 rpm

Electrical connection: 230 V*

* Other voltages on request!

3011 / 50...60 Hz, 90 W

3012 / 50 or 60 Hz**, 90 W

** Please indicate when ordering!

Net/gross weight: 18/22 kg

Packing volume (cardboard box): 0.19 m³

■ **Order No. 3011**

■ **Order No. 3012**
with RS 232 port

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring dependability for continuous operation with three-dimensional motion
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ 3011 - clearly laid-out control panel for easy operation
- ▶ 3012 - speed and remaining time indicated by two LC displays

- ▶ 3011 - electronic speed control, stepless, gentle start-up
- ▶ 3012 - microprocessor-controlled, adjustable in steps of 0.5 rpm, gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

In AIDS research, for diagnostic tests with test plates, or for growing cell cultures and micro-organisms this unit has become indispensable.

Also well-suited for use in laboratories, incubation rooms and moderating rooms at ambient temperatures between +10 °C and +50 °C.

Dependable and long-lasting

These versatile Shakers use their slow and uniform rocking motion to create reproducible growth and processing conditions at low speeds for cell cultures and other media.

This permits ideal rinsing and tumbling of the samples. Both of these units are maintenance-free, carry the GS safety approval and come with the CE mark.



Technical Data

Overall dimensions (W x D x H):
510 x 625 x 168 mm

Moving platform: 450 x 450 mm

Load: max.15 kg

Shaking motion: rocking

Timer:

3013 / up to 60 minutes, or continuous operation

3014 / 1 min. - 99:59 hours, or continuous operation

Rocking amplitude: 3 degrees

Rocking frequency: 2 - 50 rpm

Electrical connection: 230 V*

* Other voltages on request!

3013 / 50...60 Hz, 90 W

3014 / 50 or 60 Hz**, 90 W

** Please indicate when ordering!

Net/gross weight: 18/21 kg

Packing volume (cardboard box): 0.19 m³

■ Order No. 3013

■ Order No. 3014
with RS 232 port



3013 Analogue Rocking Motion Shaker with Platform Frame 3968

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring dependability for slow rocking motion
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ 3013 - clearly laid-out control panel for easy operation
3014 - speed and remaining time indicated by two LC displays

- ▶ 3013 - electronic speed control, stepless, gentle start-up
3014 - microprocessor-controlled, adjustable in steps of 0.5 rpm, gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

This model has proven itself through reliable and perfect work, also for continuous operation, and is always called upon when the best possible supply of parallel cultures and cell lines is required, or for staining or discoloration of gels.

Both of these units are well-suited for use in laboratories, incubation rooms and moderating rooms at ambient temperatures between +10 °C and +50 °C.

3015 / 3017

■ Universal and untiring

A silent operating and universally applicable Orbital Shaker that exhibits its untiring strength in particular for gentle motion and vigorous shaking of liquids. Both of these units are maintenance-free, carry the GS safety approval and come with the CE mark.



Technical Data

Overall dimensions (W x D x H):
510 x 625 x 142 mm

Moving platform: 450 x 450 mm

Load: max. 15 kg

Shaking motion: orbital

Timer:

3015 / up to 60 minutes, or continuous operation

3017 / 1 min. - 99:59 hours, or continuous operation

Shaking amplitude: 30 mm

Shaking frequency: 20 - 300 rpm

Electrical connection: 230 V*

* Other voltages on request!

3015 / 50...60 Hz, 65 W

3017 / 50 or 60 Hz**, 65 W


** Please indicate when ordering!

Net/gross weight: 18/22 kg

Packing volume (cardboard box): 0.19 m³

■ Order No. 3015

■ Order No. 3017
with RS 232 port



Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for orbital shaking motion
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ 3015 - clearly laid-out control panel for easy operation
- ▶ 3017 - speed and remaining time indicated by two LC displays
- ▶ 3015 - electronic speed control, stepless, gentle start-up
- ▶ 3017 - microprocessor-controlled, adjustable in steps of 1.0 rpm, gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

What counts when growing micro-organisms, cell and tissue cultures is a „reliable colleague“ - an indispensable ingredient for successful work in bio-chemistry, microbiology, biotechnology, bacteriology and virology.

Both of these units are particularly well-suited for use in laboratories, incubation rooms and moderating rooms in ambient temperatures between +10 °C and +50 °C.



3015 Analogue Orbital Shaker with Tray 3966 and Clamps for Erlenmeyer flasks 3983 - 3990

3016 / 3018

Robust and variable

Versatile, powerful and exceptionally quiet - those are the descriptive qualities of this robust Shaker with reciprocating (back-and-forth) motion. Use of this device is recommended for vigorous and intensive shaking of clamped lying flasks, mixing flasks or separating funnels in continuous operation. Both of these units are maintenance-free, carry the GS safety approval and come with the CE mark.



Technical Data

Overall dimensions (W x D x H):
510 x 625 x 145 mm

Moving platform: 450 x 450 mm

Load: max.15 kg

Shaking motion: reciprocating

Timer:

3016 / up to 60 minutes, or continuous operation

3018 / 1 min. - 99:59 hours, or continuous operation

Shaking amplitude: 30 mm

Shaking frequency: 20 - 300 rpm

Electrical connection: 230 V*

* Other voltages on request!

3016 / 50...60 Hz, 65 W

3018 / 50 or 60 Hz**, 65 W

** Please indicate when ordering!

Net/gross weight: 18/22 kg

Packing volume (cardboard box): 0.19 m³

■ Order No. 3016

■ Order No. 3018

with RS 232 port



3016 Analogue Back-and-forth Shaker with Tray 3966 and Test Tube Racks 3953

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for reciprocal shaking motion
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment
- ▶ an a.c. motor with overload protection drives the unit
- ▶ 3016 - clearly laid-out control panel for easy operation
3018 - speed and remaining time indicated by two LC displays

- ▶ 3016 - electronic speed control, stepless, gentle start-up
3018 - microprocessor-controlled, adjustable in steps of 1.0 rpm, gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

The producers of suspensions and emulsions know this shaker well. The shaking platform's jerky back-and-forth motion creates high turbulence, thus thoroughly mixing the media. This is a vital prerequisite, for example, in medical diagnostics, or in foodstuffs or environmental analyses.

Both of these units are well-suited for use in laboratories, incubation rooms and moderating rooms in ambient temperatures between +10 °C and +50 °C.

3019 / 3020

Technical Data

Overall dimensions (W x D x H):
745 x 730 x 135 mm

Moving platform: 676 x 540 mm

Load: max. 30 kg

Shaking motion: orbital

Timer:

3019 / up to 60 minutes, or continuous operation

3020 / 1 min. - 99:59 hours, or continuous operation

Shaking amplitude: 32 mm

Shaking frequency: 20 - 250 rpm

when the rack frame is used: 20 - 200 rpm

Electrical connection: 230 V*

* Other voltages on request!

3019 / 50...60 Hz, 90 W

3020 / 50 or 60 Hz**, 90 W

** Please indicate when ordering!

Net/gross weight: 34/40 kg

Packing volume (cardboard box): 0.35 m³

■ Order No. 3019

■ Order No. 3020

with RS 232 port

■ Indispensable and powerful

A dependable, long-life Orbital Shaker with a large shaking tray for accommodating heavier loads. A universally applicable, quiet unit, indispensable in the growing of micro-organisms, cell and tissue cultures.

This unit is well-suited for gentle motion or vigorous mixing of the most varying liquids, even in continuous operation, thanks to its useful shaking amplitude and the option of adjusting its speed. Both of these units are maintenance-free, carry the GS safety approval and come with the CE mark.



3019 Analogue Orbital Shaker with Rack Frame 3981, Trays 3980 (2), Test Tube Racks 3953 and Clamps for Erlenmeyer flasks 3983 - 3990

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate and the

shaking platform are made of electrolytically galvanised, powder-coated sheet steel. The shaking platform is equipped with four support rods with screw-type clamps for secure attachment of accessory equipment

- ▶ a special rubber pad ensures a non-slip grip of objects on the shaking tray
- ▶ an a.c. motor with overload protection drives the unit
- ▶ 3019 - clearly laid-out control panel for easy operation
3020 - speed and remaining time indicated by two LC displays
- ▶ 3019 - electronic speed control, stepless, gentle start-up
3020 - microprocessor-controlled, adjustable in steps of 1.0 rpm, gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications


Impressive references. For this powerful orbital shaker leaves a lasting impression everywhere it has been used, for example, for analytical or diagnostic applications in the pharmaceutical industry, chemistry, biology, or in plant breeding or nutritional applications.

Both of these units are well-suited for use in laboratories, incubation rooms and moderating rooms in ambient temperatures between +10 °C and +50 °C.

Fast and efficient

This Shaker's high speed and its low shaking amplitude guarantee the best possible mixing, even in the smallest test flasks.

The basic equipment for this vibration shaker with orbital motion includes a frame holder for up to six test plates. This unit is maintenance-free, carries the GS safety approval and comes with the CE mark.



Technical Data

Overall dimensions (W x D x H):
380 x 510 x 125 mm

Moving platform: 330 x 330 mm

Load: max.1.2 kg

Shaking motion: orbital / vibrating

Timer: up to 60 minutes, or continuous operation

Shaking amplitude: 3 mm

Shaking frequency: 100 - 1450 rpm

Electrical connection:

230 V* 50...60 Hz, 65 W

* Other voltages on request!

Net/gross weight: 11/15 kg

Packing volume (cardboard box): 0.1 m³

■ **Order No. 3023**

Features

- ▶ compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for continuous operation
- ▶ housing made of high impact strength polystyrene, off-white varnish. The base plate is made of electrolytically galvanised, powder-coated sheet steel, the shaking platform of anodised aluminium, equipped with four plastic pins for secure attachment of accessory equipment (on request) and a frame holder for six test plates (supplied as standard)
- ▶ an a.c. motor with overload protection drives the unit
- ▶ clearly laid out control panel for easy operation

- ▶ electronic speed control, stepless, with gentle start-up
- ▶ constant speed during continuous operation, independent of load

Applications

Reliable, versatile, efficient - the characteristics that make this Shaker so interesting for use in medical diagnostics, biotechnology or microbiology.

This unit is well-suited for use in laboratories, incubation rooms and moderating rooms in ambient temperatures between +10 °C and +50 °C.

3025

Smooth und exact

This Test Tube Rotating Shaker is particularly well-suited for gentle to intensive shaking and mixing of powdered or liquid substances, thanks to its constant, uniform rotating tilting motion. The axle can be removed and can also be loaded outside of the rotator.

This unit is maintenance-free, carries the GS safety approval and comes with the CE mark.



Technical Data

Overall dimensions (W x D x H):
490 x 330 x 220 mm

Revolutions: 6 - 60 rpm

Rotating axle: can accommodate a max. of 24 test tubes, 12-17 mm diameter, tube lengths between 75 und 180 mm

Shaking motion: orbital rotating

Electrical connection:
230 V* 50...60 Hz, 80 W
* Other voltages on request!

Net/gross weight: 10/12 kg

Packing volume (cardboard box): 0.1 m³

Order No. 3025

Features

- ▶ compact, low-wear drive mechanism
- ▶ housing made of electrolytically galvanised, powder-coated sheet steel, the axle and collecting trough are made of stainless steel
- ▶ clearly laid out control panel for easy operation
- ▶ electronic speed control, stepless
- ▶ Optionally, the rotator can be equipped without surcharge with an alternative axle, including one set of clamps (on request). Now it is possible to fasten clamps of different sizes, for example for reaction vessels Ø 10 mm or even 50 ml Falcon Tubes Ø 30 mm.

Applications

Smooth and exact motion - that is what this rotator model guarantees when it comes to separating and/or mixing applications.

This unit is well-suited for use in laboratories, incubation rooms and moderating rooms in ambient temperatures between +10 °C and +50 °C.

Special and tried and true

The „specialist“ among the Orbital Rotators for every-day use. Use of this robustly designed unit is easy and its uses are multifarious, for example when soil samples must be exactly settled, mixed and processed. The unit is maintenance-free, carries the GS safety approval and comes with the CE mark.

Technical Data

Overall dimensions (W x D x H):
770 x 700 x 715 mm

Load: max. 20 kg
with uniform load distribution

Motion: orbital rotating

Capacity: max. 12 bottles / vessels

Bottle/vessel dimensions:
max. 110 mm diameter, round or square /
rectangular, max. 270 mm height

Shaking frequency: 1 - 20 rpm

Electrical connection:
230 V* 50...60 Hz, 100 W
* Other voltages on request!

Net/gross weight: 62/78 kg

Packing volume (cardboard box): 0.91 m³

Order No. 3040



Features

- ▶ compact, low-wear drive mechanism
- ▶ housing made of electrolytically galvanised, powder-coated sheet steel
- ▶ a d.c. motor with overload protection drives the unit
- ▶ electronic speed control, stepless
- ▶ constant speed during continuous operation
- ▶ clearly laid out control panel for easy operation: main switch with control lamp, rotary selector switch for setting and LED display for speed indication and lever for the stopping device of the rotating rack, which guarantees easy clamping of the sample vessels

- ▶ rotating rack with ball bearings on both sides, able to accommodate a max. of 12 flasks/vessels, round or square/rectangular, up to a diameter of 110 mm and a height of 270 mm, in four planes, each plane with three holding frames. Drive is implemented via a toothed belt and a sliding hub.
- ▶ holding frame for safe, secure clamping of the sample vessels, made of stainless steel

Applications

The uniform rotating motion of this special Shaker make it particularly well-suited for processing soil samples in glass/plastic wide-mouth vessels with up to 2000 ml rated volume as per DIN 38414, Part 4 „German Standard Methods for Water, Wastewater and Sludge Analysis - Determination of Leachability by Water“ .

This unit can be used in ambient temperatures between +10 °C and +40 °C.

Accessories



3005



3006



Shaking tray

made of stainless steel, 330 x 330 mm, with holes to accommodate clamps for Erlenmeyer flasks and other accessory equipment

Order No. 3950



Clamps

made of stainless steel for Erlenmeyer flasks, for screwing on to shaking tray 3950, complete with attachment materials

- Order No. 3983** for 25 ml flasks (45*)
- Order No. 3984** for 50 ml flasks (25*)
- Order No. 3985** for 100 ml flasks (16*)
- Order No. 3986** for 200 ml flasks (12*)
- Order No. 3987** for 250-300 ml flasks (9*)
- Order No. 3988** for 500 ml flasks (9*)
- Order No. 3989** for 1000 ml flasks (4*)
- Order No. 3990** for 2000 ml flasks (2*)

Other clamps on request

* max. number of clamps per shaking tray



Test tube rack

made of stainless steel, for test tubes; perforated section can be tilted by 90°, with clamping springs for secure grip and silent shaking of glasses; can be screwed on to shaking tray 3950

Order No. 3953

for a max. of 24 tubes: 12 - 17 mm diameter
Capacity of tray: three test tube racks



Clamps

made of stainless steel, for separating funnels, for screwing on to shaking tray 3950

Order No. 3957 for 50 ml separating funnels (6*)
(ISO/Squibb, neck 19/26)

Order No. 3958 for 100 ml separating funnels (6*)
(ISO/Squibb, neck 19/26)


Order No. 3959 for 250 ml separating funnels (4*)
(ISO/Squibb, neck 19/26)

Order No. 3955 for 250 ml separating funnels (4*)
(conical form, neck 29/32)

Order No. 3956 for 500 ml separating funnels (3*)
(ISO/Squibb, neck 29/32)

Other clamps on request

* Max. number of clamps per shaking tray



Holding frame

made of stainless steel, for attachment of a test plate, for screwing on to shaking tray 3950, complete with attachment materials

Order No. 3910

Capacity of tray: four test plates



Non-slip mat

for the shaking platform, 300 x 300 mm size, for slow moving, e.g. nutrient solutions in Petri dishes and flasks

Order No. 3951



Universal mount

for secure attachment of different shaking objects between the four rubber-coated bars

Order No. 3952

Accessories



3011



3012



3013



3014



Order No. 3966

Shaking tray
made of stainless steel, 450 x 450 mm, with holes to accommodate clamps for Erlenmeyer flasks and other accessory equipment



Clamps
made of stainless steel for Erlenmeyer flasks, for screwing on to shaking tray 3966, complete with attachment materials

- Order No. 3983 for 25 ml flasks (79*)
- Order No. 3984 for 50 ml flasks (49*)
- Order No. 3985 for 100 ml flasks (36*)
- Order No. 3986 for 200 ml flasks (22*)
- Order No. 3987 for 250-300 ml flasks (16*)
- Order No. 3988 for 500 ml flasks (12*)
- Order No. 3989 for 1000 ml flasks (9*)
- Order No. 3990 for 2000 ml flasks (4*)

Other clamps on request

* Max. number of clamps per shaking tray



Order No. 3965

Non-slip mat
for the shaking platform, 420 x 420 mm size, for slow moving, e.g. nutrient solutions in Petri dishes



Order No. 3967

Universal mount
for secure attachment of different shaking objects between the six rubber-coated bars



Order No. 3968

Platform frame
with four levels, with top rims, three levels removable. Frame and trays made of stainless steel. Distance between trays - 60 mm. Grooved rubber mats on trays to ensure secure grip of objects.

Accessories



3015



3017



3016



3018



Shaking tray
made of stainless steel,
450 x 450 mm, with holes
to accommodate clamps for
Erlenmeyer flasks and other
accessory equipment

Order No. 3966




Clamps
made of stainless steel for
Erlenmeyer flasks, for screwing
on to shaking tray 3966,
complete with attachment
materials

- Order No. 3983 for 25 ml flasks (79*)
- Order No. 3984 for 50 ml flasks (49*)
- Order No. 3985 for 100 ml flasks (36*)
- Order No. 3986 for 200 ml flasks (22*)
- Order No. 3987 for 250-300 ml flasks (16*)
- Order No. 3988 for 500 ml flasks (12*)
- Order No. 3989 for 1000 ml flasks (9*)
- Order No. 3990 for 2000 ml flasks (4*)

Other clamps on request

* Max. number of clamps per shaking tray



Test tube rack
made of stainless steel, for test
tubes; perforated section can be
tilted by 90°, with clamping
springs for secure grip and silent
shaking of glasses; can be
screwed on to shaking tray 3966

Order No. 3953
for a max. of 24 tubes: 12 - 17 mm diameter
capacity of tray: six test tube racks



Clamps
made of stainless steel, for
separating funnels, for screwing
on to shaking tray 3966

- Order No. 3957 for 50 ml separating funnels (11*)
(ISO/Squibb, neck 19/26)
- Order No. 3958 for 100 ml separating funnels (11*)
(ISO/Squibb, neck 19/26)
- Order No. 3959 for 250 ml separating funnels (8*)
(ISO/Squibb, neck 19/26)
- Order No. 3955 for 250 ml separating funnels (8*)
(conical form, neck 29/32)
- Order No. 3956 for 500 ml separating funnels (6*)
(ISO/Squibb, neck 29/32)

Other clamps on request
* Max. number of clamps per shaking tray


Holding Frame
made of stainless steel, for attachment of a test plate, for screwing
on to shaking tray 3966, complete with attachment materials
pict. see Shakers 3019 - 3020

Order No. 3910
Capacity of tray: six test plates



Non-slip mat
for the shaking platform,
420 x 420 mm size, for slow
moving, e.g. nutrient solutions
in Petri dishes

Order No. 3965




Universal mount
for secure attachment of
different shaking objects
between the six rubber-
coated bars

Order No. 3967

Accessories



3019



3020

Shaking tray

made of 3-mm-thick anodised aluminium, 670 x 537 mm, with holes to accommodate clamps for Erlenmeyer flasks and other accessory equipment



Order No. 3980

Clamps

made of stainless steel for Erlenmeyer flasks, for screwing on to shaking tray 3980, complete with attachment materials




- Order No. 3983** for 25 ml flasks (99*)
- Order No. 3984** for 50 ml flasks (99*)
- Order No. 3985** for 100 ml flasks (50*)
- Order No. 3986** for 200 ml flasks (26*)
- Order No. 3987** for 250-300 ml flasks (26*)
- Order No. 3988** for 500 ml flasks (26*)
- Order No. 3989** for 1000 ml flasks (12*)
- Order No. 3990** for 2000 ml flasks (9*)

Other clamps on request

* Max. number of clamps per shaking tray

Test tube rack

made of stainless steel for test tubes; perforated section can be tilted by 90°, with clamping springs for secure grip and silent shaking of glasses; can be screwed on to shaking tray 3980



Order No. 3953

for a max. of 24 tubes: 12 - 17 mm diameter
Capacity of tray: nine test tube racks



Holding frame

made of stainless steel, for attachment of a test plate, for screwing on to shaking tray 3980, complete with attachment materials

Order No. 3910

Capacity of tray: fifteen test plates

Universal mount

for secure attachment of shaking objects. The mount consists of two longitudinal bars and six transverse bars. Screw-type clamps are used for adjusting the longitudinal bars vertically and transverse bars horizontally.



Order No. 3982

Rack frame

for doubling the capacity by accommodating two shaking trays 3980; distance between trays - 205 mm. The bottom tray can be loaded with flasks up to a max. of 500 ml.



Order No. 3981



瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號

信件請寄：高雄市郵政信箱1394號

Tel : 07-7169249 Fax : 07-2134620

Weizhou International Co.,Ltd

Address : No. 24, Lane 135 Wu-de St.,Kaohsiung City, Taiwan ROC 80647

Mailing : P. O. Box 1394 kaohsiung City, Taiwan ROC

Tel : 886-7-7169249 Fax : 886-7-2134620

E-MAIL : instrument@weizhou.com.tw

<http://www.weizhou.com.tw/instrument/i-Index.htm>

Line : weizohu1995 Skype : service450429 QQ : 1467808036