



農業曳引機

WE-260 BT GOLDPOWER 4x2 MINIMAX 機型



SPECIFICATION		DESCRIPTION
ENGINE		260 BT GOLDPOWER 4x2 MINIMAX
Emission		Stage IIIA
Make / Type		BOZOK ENGINE / 1003D
Number of Cylinders / Aspiration		3 / Turbo Intercooler
Displacement		2990 cm3
Air Filter		Dry Type
PERFORMANCE		
Maximum Engine Power (ISO)		67 HP (49 kw)
Nominal Engine Speed		2200 d/d (rpm)
Maximum Torque		250 Nm / 1500 d/d (rpm)
CLUTCH		
PTO	Type	Dry Dual Clutch
	Disc Diameter	254 mm – 304 mm (10"-12")
IPTO	Type	Dry Single Clutch
	Disc Diameter	305 mm (12")
STEERING		
Type		Hydrostatic
Maximum Steering Angle		55°
Turning Circle Without Braking		10500
TRANSMISSION		
Type of Transmission		Standard
Gear Option		8 Forward 2 Reverse

Optional Gear Option	N/A
Drive	Direct
Mechanical 4WD Engagement	o
Differential Lock	Mechanical
Differential Lock	29 km/h
POWER TAKE-OFF (PTO)	
Mechanical Clutch (PTO)	•
540 rpm PTO Speed @ 1790 rpm	•
Independent Hydraulic Clutch	?/•
Ground Speed PTO	?/•
PTO Power (ISO)	56 HP @ 2250
BRAKES	
Type	Disc Brakes
Pedals	Classic or Pendant Pedal

HYDRAULIC SYSTEM

Draft Control	•
Position Control	•
Accuracy Control	•
Maximum Pump Flow	17-22 lt/dk (lt/min)
Maximum Pump Pressure	215 bar
Maximum Lifting Capacity	2000 kg
External Pump Flow	42lt/dk (lt/min) / 175 Bar
Spool Valve	o / •

CAPACITIES

Fuel Tank	48 lt
Oil Sump	7.5 lt
Coolant	18 lt
Transmission & Hydraulics	38 lt
Steering	2 lt

MASSES AND DIMENSIONS

Total Mass with ballast (kg)	2600
Front Masses (kg)	(6x20 Kg) – (Çekili ağırlık 1x36 Kg)
Rear Masses (kg)	(2x40 Kg)
A Front Axle Ground Clearance	330 mm

B	Front Track Width	1305 mm
C	Overall Width	1425 mm
D	Rear Track Width	1300 mm
E	Wheelbase	2160 mm
F	Rear Overhang	822 mm
G	Front Overhang	810 mm
H	Overall Length	3792 mm
I	Overall Height	2350 mm
J	Hood-Top Height	1250 mm
L	Folded ROPS Height	1370 mm
K	Buffer Ground Clearance	485 mm
M	Rear Tow ground Clearance	330 mm
	Front Tyres	280/70R16
	Rear Tyres	14.9/13,24



A Division of Ken-Ding Group

瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街 135 巷 24 號

信件請寄：高雄市郵政信箱 1394 號

Tel：07-7169249 Fax：07-2134620

Weizhou International Co., Ltd

Address：No. 24, Lane 135 Wu-de St., Kaohsiung City, Taiwan ROC80647

Mailing：P. O. Box 1394 kaohsiung City. Taiwan ROC

Tel：886-7-7169249 Fax：886-7-2134620

E-MAIL：agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/Tractor/index-import.htm>

 **QQ**：1467808036

 **SKYPE**：service450429

 **LINE**：weizhou1995

 **Wechat**：walterhsu1995

 **Viber**：+886972326392

 **WhatsApp**：+886972326392